

6173-20US

recovered user terminal;

sending a subscription message from a the new or recovered user terminal to the registrar, a header in the subscription message containing a unique indication of a particular user; and in response to said subscription message containing a unique indication in a header, returning a notification message to the new or recovered user terminal, the payload of said notification message including said service information for which allows the user to continue at least some of their ongoing ~~be used by the user terminal~~ for communication services at the new or recovered user terminal.

2. (Original) The method as claimed in claim 1, wherein the user has a plurality of ongoing communication services at the time that the subscription message containing a unique indication in a header is sent.
3. (Original) The method as claimed in claim 2, wherein the payload of said notification message includes service information for each one of said ongoing communication services.
4. (Currently Amended) The method as claimed in claim 1, wherein said new or recovered user terminal comprises a recovered user terminal and said subscription message is sent after said recovered user terminal experiences a failure.
5. (Original) The method as claimed in claim 4, wherein said service information

6173-20US

included in the payload of said notification message enables recovery of communication services to their state at the time of said terminal failure.

6. (Currently Amended) The method as claimed in claim 1, wherein said new or recovered user terminal comprises a new user terminal and said subscription message is sent by a said new user terminal after said user switches terminals from a previous user terminal to said new user terminal.

7. (Currently Amended) The method as claimed in claim 6, wherein said new user terminal is a different type of ~~mobile~~ user terminal than said previous ~~mobile~~ user terminal.

8. (Original) The method as claimed in claim 1, wherein said communication services include a push service and the registrar is a push proxy.

9. (Currently Amended) The method as claimed in claim 8, wherein said push proxy automatically stores said service information in the registrar when the user terminal subscribes to said communication services.

10. (Currently Amended) A network architecture, comprising:
a plurality of user terminals;
a radio access network, said radio access network containing elements providing information indicating the presence, status and/or location of said plurality of user terminals;

6173-20US

a presence server, said presence server adapted to receive said information indicating the presence, status and/or location of said plurality of user terminals;

at least one communication service provider providing a plurality of communication services; and

a proxy server, said proxy server adapted to provide said plurality of communication services to said plurality of user terminals upon subscription thereto, wherein the proxy server stores and maintains service information which is related to said plurality of communication services and allows a user to continue their ongoing communication services at a new or recovered user terminal, and which provides said service information in a single message sent in response to a request therefore from a new or recovered user terminal, and wherein when said proxy server receives said request from a new or recovered user terminal, said proxy server resubscribes the user to ongoing subscriptions for which service information is stored therein.

11. (Currently Amended) The network architecture as claimed in claim 10, wherein said proxy server provides said service information in the payload of a notification message sent to the requesting new or recovered user terminal in response to said request.

12. (Original) The network architecture as claimed in claim 11, wherein said presence server, said proxy server and said plurality of user terminals send messages to each other according to the Session Initiation Protocol (SIP) and the notification message comprises a SIP NOTIFY response.

6173-20US

13. (Original) The network architecture as claimed in claim 12, wherein said request comprises a SIP SUBSCRIBE message.
14. Cancelled.
15. (Currently Amended) The network architecture as claimed in claim 11, wherein said new or recovered user terminal comprises a recovered user terminal and said recovered user terminal sends said request after it experiences failure.
16. (Currently Amended) The network architecture as claimed in claim 11, wherein said new or recovered user terminal comprises a new user terminal and, when a user switches to said new user terminal from a previous user terminal, the new user terminal sends said request to said proxy server.
17. (Original) The network architecture as claimed in claim 16, wherein the new user terminal is a different type of user terminal than said previous user terminal.
18. (Original) The method as claimed in claim 1, wherein said registrar comprises a SIP registrar, said subscription message comprises a SIP SUBSCRIBE message, said header comprises an event header, and said notification message comprises a SIP NOTIFY response.
19. (Original) The method as claimed in claim 18, wherein the user has a plurality of

6173-20US

ongoing communication services at the time that the SIP SUBSCRIBE message containing a unique indication in the event header is sent.

20. (Original) The method as claimed in claim 19, wherein the payload of said SIP NOTIFY response includes service information for each one of said ongoing communication services.
21. (Currently Amended) The method as claimed in claim 18, wherein said new or recovered user terminal comprises a recovered user terminal and said SIP SUBSCRIBE message is sent after said recovered user terminal experiences a failure.
22. (Original) The method as claimed in claim 21, wherein said service information included in the payload of said SIP NOTIFY response enables recovery of communication services to their state at the time of said terminal failure.
23. (Currently Amended) The method as claimed in claim 18, wherein said new or recovered user terminal comprises a new user terminal and said SIP SUBSCRIBE message is sent by a said new user terminal after user switches terminals from a previous mobile user terminal to said new user terminal.
24. (Currently Amended) The method as claimed in claim 23, wherein said new user terminal is a different type of mobile user terminal than said previous mobile user terminal.

6173-20US

25. (Original) The method as claimed in claim 18, wherein said communication services include a push service and the SIP registrar is a push proxy.
26. (Currently Amended) The method as claimed in claim 25, wherein said push proxy automatically stores said service information when the user ~~terminal~~ subscribes to said communication services.
27. (Currently Amended) A proxy server, said proxy server being adapted to:
provide a plurality of communication services to a plurality of user terminals upon subscription of said user terminals to said communication services;
store and maintain service information which is related to said plurality of communication services and allows a user to continue their ongoing communication services at a new or recovered user terminal;
provide said service information in a single message sent in response to a request therefore from a new or recovered user terminal; and;
when said proxy server receives said request from ~~one of~~ said new or recovered user terminal, the proxy server re-subscribes the user to ongoing subscriptions for which service information is stored therein.
28. (Currently Amended) The proxy server as claimed in claim 27, wherein said proxy server provides said service information in the payload of a notification message to the requesting new

6173-20US

or recovered user terminal.

29. (Previously Amended) The proxy server as claimed in claim 28, wherein the proxy server sends and receives messages according to the Session Initiation Protocol (SIP) and the notification message comprises a SIP NOTIFY response.

30. (Original) The proxy server as claimed in claim 29, wherein said request comprises a SIP SUBSCRIBE message.

31. Cancelled.

32. (Currently Amended) A mobile terminal, said mobile terminal being adapted to:
receive a plurality of communication services;
send a subscription message to a registrar, a header in the subscription message containing a unique identification of a particular user;
receive a notification message sent from said registrar in response to said subscription message, the payload of said notification message including service information which allows said particular user to continue to receive for said a plurality of their communication services at said mobile terminal; and

using said service information included in the payload of said notification message to continue said plurality of communication services at said mobile terminal.

6173-20US

33. (Original) The mobile terminal as claimed in claim 32, wherein said subscription message is sent after said mobile terminal experiences a failure.
34. (Original) The mobile terminal as claimed in claim 33, wherein said service information included in the payload of said notification message enables recovery of communication services to their state at the time of said mobile terminal failure.
35. (Original) The mobile terminal as claimed in claim 32, wherein said subscription message is sent by said mobile terminal after said user switches to said mobile terminal from a previous mobile terminal.
36. (Original) The mobile terminal as claimed in claim 32, wherein said subscription message is a SIP SUBSCRIBE message, said header is an event header in the SIP SUBSCRIBE message and said notification message is a SIP NOTIFY response.
37. (Previously Added) The method as claimed in claim 1, wherein the unique indication comprises an event name particular to a specific user.
38. (Previously Added) The method as claimed in claim 1, wherein the unique indication comprises identification of the particular user.
39. (Previously Added) The mobile terminal as claimed in claim 32, wherein the unique

6173-20US

identification comprises an event name particular to a specific user.

40. Cancelled.

10

BRMFS1 451623v1